

19" / 1 RU with 15", 17" or 19" LCD

	15"	17"
Resolution	1024 x 768	1280 x 1024
Display Area (W x H)	304.1 x 228.1 mm	337.9 x 270.3 mm
Contrast Ratio (typ.)	500 : 1	500 : 1
Display Color	16.2M	16.2M
Brightness (typ.)	250 cd/m ²	300 cd/m ²
Viewing Angle H / V (typ.)	-70°~70° / -60°~60°	-75°~75° / -60°~75°
Power Consumption	33 Watt	38 Watt

	19"
Resolution	1280 x 1024
Display Area (W x H)	376.3 x 301.1 mm
Contrast Ratio (typ.)	1300 : 1
Display Color	16.7M
Brightness (typ.)	300 cd/m ²
Viewing Angle H / V (typ.)	-89°~89° / -89°~89°
Power Consumption	44 Watt

Signal Connector	1 x VGA Input, 15 pin D-Sub
optional	1 x DVI-D-Input
Interfaces	PS/2 Keyboard PS/2 Mouse
Keyboard	88-Key US-engl. 88-Key German
Numerical Key Pad	17-Key
Touch Pad	integrated
On-Screen Display	Contrast, Brightness, H/V Position, H/V Size, H-scaling, Auto-adjust, Color Temp. (9300, 6500, User), Red-Gain, Blue-Gain, Green-Gain, Gamma, Recall, Phase, Channel, OSD exit
Power Input	12 V _{DC}
Power Supply	integrated, 100~240 V _{AC}
Dimensions (W x H x D)	483 x 44.5 x 544 mm
Operating Temperature	0°~50° C

OPTIONS	
8 Port KVM-Switch	8 x "3-in-1" (keyboard + video + mouse) 15 pin D-Sub connector
16 Port KVM-Switch	16 x "3-in-1" (keyboard + video + mouse) 15 pin D-Sub connector
Ethernet Remote Control	10/100 Mbit/s, RJ-45



The perfect console solution including a fold-out LCD for 19" rackmount applications: it only takes 1 RU of rack space!

Available in US-engl. or german keyboard layout