



## Supports Analog RGB, Panel Link, and Broadband

VD-1627 is a video signal distributor that supports analog plug connectors that comply with DVI standards. This unit distributes analog video signals and low-voltage digital serial (panel link) video signals to 5 lines

### Features

- Supports DVI compliant connectors, enabling distribution of analog and digital serial video signals.
- Supports broadband DC to 200 MHz for analog video signals, and 25 to 162 MHz for digital signals.
- Electable analog sync signal input between 75Ω terminal and high impedance.
- DDC-2B support possible (OUTPUT-1 only).

### specifications

<b>Number of I/O</b>	5 distributions from 1 input
<b>Analog input</b>	
<b>Video signal</b>	R,G,B to 1.0V (75Ω terminal) DC to 200MHz
<b>Sync signal</b>	HS,VS to 2V (75Ω terminal)
<b>Digital input</b>	
<b>Input format</b>	Panel link 25 to 162MHz
<b>Analog output</b>	
<b>Video signal</b>	R,G,B to 1.0V (75Ω terminal) ΩDC to 200MHz
	Output level: According to inut signal.
<b>Sync signal</b>	HS,VS output level: According to inut signal.
<b>Digital output</b>	
<b>Output format</b>	Panel link 25 to 162MHz
<b>General specification</b>	
<b>Voltage</b>	AC90 to 250V (50/60 Hz)
<b>Power consumption</b>	20W(AC100V)
<b>Operating temperature range</b>	5 to 40°C (no condensation)
<b>Operating humidity range</b>	30 to 80%RH (no condensation)
<b>Dimensions</b>	430(W) x 44(H) x 330(D) mm (1U/excluding projected parts)
<b>Weight</b>	Approx. 3kg

### Rear View VD-1627

