

Numero Ordine: 23120472

Campo testo libero 2: 12,1 Zoll (4:3) Panel-PC, Intel Celeron N6211

Produttore: TL Electronic

Peso: 6 kg


R12IB3S-OFM2_PMA

Prezzo su richiesta

 Prezzi più IVA [più spese di spedizione](#)

Tempi di consegna: su richiesta

Informazione prodotto "R12IB3S-OFM2_PMA"

Built-in Panel PC for professional use Industrial Panel PC in sturdy steel sheet design Robust aluminium front panel (IP65 protected) Designed for industrial applications in continuous operation Panelmount installation with rear screwed bolts Long-term availability

article group specification:	2312
Manufacturer:	WM
Manufacturer:	Winmate
series name:	SlimLine-Serie
Manufacturer item number:	R12IE3S-OFM2
mechanics:	Panel Mount
dimensions width:	34
dimensions height:	29
dimensions depth:	5,7
Material housing:	Stahlblech / steel sheet
Material Front :	Aluminium / aluminum
protection front:	IP65
colour:	RAL 7035 / light grey
controls:	2 Keys: Power, Reset
VESA-Mounting Interface:	VESA 75 x 75 mm
mounting:	Einbau von vorne / front installation
cooling:	lüfterlos / fanless
Display-diagonal (inch):	12,1
aspect ratio:	4:3
resolution:	1024 x 768
brightness:	500 cd/m ²
contrast:	1000:1

Display-Technologie:	LCD, LED Backlight
Touch-Screen or glass:	Resistive / Glas (optional)
Touch Interface:	USB
Manufacturer controller:	Premier
voltage input DC:	12 V/DC
external power supply:	12 V/DC, 100 - 240 V/AC, DC plug
HDMI:	1 x HDMI 2.0 (optional)
USB:	2 x USB 3.2 Gen2x1 (Type-A)
serial:	2 x RS232
Audio:	2 x Speaker
LAN:	2x 2.5 Giga LAN RJ45
CPU Typ:	Celeron
CPU Model:	N6211
CPU 64bit:	Ja
CPU speed:	1,2 GHz
CPU cores:	2
CPU socket:	FCBGA1493
RAM size (MB):	8192
RAM max. size (MB):	16384
Grafik Controller:	Intel UHD Graphics for 10th Generation
safety:	TPM 2.0
SSD capacity (GB):	128
Ethernet connections:	2 x RJ-45
Ethernet data transfer:	2 x Gigabit-LAN
Ethernet Controller :	2 x Intel Ethernet Controller
WLAN :	Optional / optional
Bluetooth :	optional / optional
Betriebssystem:	Optional
operating-system language version:	deutsch / english / italian
operating temperatur min.:	0°C
operating temperatur max.:	50°C
warranty:	24 Monate / 24 months

Link correlati a "R12IB3S-OFM2_PMA"

- [- Avete domande relative a questo prodotto?](#)
- [- Ulteriori prodotti di TL Electronic](#)

Download disponibili:

[Download Drawing Panel-PC R12IE3S-OFM2_PMA \(Panelmount\) 260521.pdf](#)