

Numero Ordine: 25140012
Campo testo libero 1: -1
Campo testo libero 2: 14,0 Zoll Rugged Industrie-Tablet-PC, Intel Core i5-1235U, Windows 11
Produttore: Winmate
Peso:2.4 kg

D140

Prezzo su richiesta

Prezzi più IVA più spese di spedizione

Pronto per la spedizione di oggi,
tempo di consegna ca. 1-3 giorni lavorativi

Informazione prodotto "D140"

Rugged Tablet-PC for professional use Shock, vibration and drop protected (MIL-STD-810G) Multi-touch (PCAP) Wide range of options and accessories for data capture, communication, docking, mounting, power, peripherals and transportation The ideal partner for warehouse, logistics, automotive, outdoor, smart factory, field service etc. Long-term availability

article group specification:	2514
Manufacturer:	WM
Manufacturer:	Winmate
series name:	Rugged Industrial Tablet PC
Manufacturer item number:	D140
mechanics:	Rugged Tablet PC
dimensions width:	35,55
dimensions height:	25,07
dimensions depth:	3,21
weight:	2,4
Material housing:	Magnesium Legierung / Magnesium alloy
protection device:	IP65
colour:	Schwarz / black
cooling:	aktiv / fan cooling
Display-diagonal (inch):	14,0
resolution:	1920 x 1080
brightness:	500 cd/m²
contrast:	1000:1
Display-Technology:	LCD, LED Backlight
Touch-Screen :	Projected Capactive / Multi-Touch
usability:	Finger/ Handschuh/ finger/ glove

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de

CPU Typ:	Core i5
CPU Model:	1235U
CPU speed:	3,3 GHz
CPU cores:	10
RAM size (MB):	8192
RAM Typ:	SO-DDR5
RAM speed:	4800
SSD design:	M.2
SSD capacity:	256
SSD number:	1
safety:	TPM 2.0 und Kensington Lock
WLAN:	Ja / yes
Bluetooth:	Ja / yes
WWAN:	Optional / optional
Camera rear:	Ja / yes
Camera rear resolution:	8MP
USB:	4x USB 3.2 (Type A), 2x USB 3.0 (Type C)
LAN:	1x RJ45 - 10/100/1000 Mbps
Audio:	2 x 1 watt speaker
Power:	1x 19 V/DC, DC plug
controls:	6 Keys: Power, 5x Function
operating system:	Windows 11 IoT Enterprise LTSC
operating temperatur min.:	-10°C
operating temperatur max.:	50°C
Shock:	MIL-STD-810G Method 516.6 Procedure I
Vibration:	MIL-STD-810G Method 514.6 Procedure I
Drop:	MIL-STD-810G Method 516.6, 4 ft
voltage input DC:	19 V/DC
external power supply:	19 V/DC, 100 - 240 V/AC, DC plug
battery:	10.9V 6700 mAh Li-Polymer Battery (3S2P)

Link correlati a "D140"

- Avete domande relative a questo prodotto?
- Ulteriori prodotti di Winmate

Download disponibili:

Download Drawing Tablet-PC D140 250124.pdf

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de