

Numero Ordine: 23171909
Campo testo libero 2: 17,0 Zoll (4:3) Panel-PC, Intel Pentium N4200
Produttore: TL Electronic, Bergkirchen-Feldgeding
Peso:6.8 kg

R17IP7T-OFM1_PME

Prezzo su richiesta

Prezzi più IVA più spese di spedizione

Tempi di consegna: su richiesta

Informazione prodotto "R17IP7T-OFM1_PME"

Built-in Panel PC for professional use Industrial Panel PC in sturdy steel sheet design Robust stainless steel front panel (IP65 protected) Designed for industrial applications in continuous operation Panelmount installation with rear screwed bolts Long-term availability

article group specification:	2317
Manufacturer:	WM
Manufacturer:	Winmate
series name:	SlimLine-Serie
Manufacturer item number:	R17IP7T-OFM1
mechanics:	Panel Mount Edelstahl / stainless steel
dimensions width:	48,3
dimensions height:	39,9
dimensions depth:	7,9
weight:	6,8
Material housing:	Stahlblech / steel sheet
Material Front :	Edelstahl / stainless steel
protection front:	IP65
protection device:	IP20
colour:	Edelstahl gebürstet / brushed stainless
controls:	2 Keys: Power, Reset
VESA-Mounting Interface:	VESA 75 x 75 mm, 100 x 100 mm
mounting:	Einbau von vorne / front installation
cooling:	lüfterlos / fanless
Display-diagonal (inch):	17,0
aspect ratio:	4:3
resolution:	1280 x 1024

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de

brightness:	350 cd/m²
contrast:	1000:1
Display-Technologie:	LCD, LED Backlight
Touch-Screen or glass:	Resistive / Glas (optional)
Touch Interface:	USB
Manufacturer controller:	Premier
voltage input DC:	12 V/DC
external power supply:	12 V/DC, 100 - 240 V/AC, DC plug
VGA:	1 x VGA (optional)
HDMI:	1 x HDMI 1.4 (optional)
DisplayPort:	1 x DP 1.2
USB:	4 x USB 3.2 Gen.1x1 (Type-A)
serial:	2 x RS232
Audio:	1 x Mic-In, 1 x Line-Out, 2 x Speaker
LAN:	2x Giga LAN RJ45
CPU Typ:	Pentium
CPU Model:	N4200
CPU 64bit:	Ja
CPU speed:	1,1 GHz
CPU cores:	4
CPU socket:	FCBGA1296
RAM size (MB):	8192
RAM max. size (MB):	16384
Grafik Controller:	Intel HD Graphics 505
safety:	TPM 2.0
SSD capacity (GB):	128
Ethernet connections:	2 x RJ-45
Ethernet data transfer:	2 x Gigabit-LAN
Ethernet Controller :	2 x Intel Ethernet Controller
WLAN :	Optional / optional
Bluetooth :	optional / optional
Betriebssystem:	Optional
operating-system language version:	deutsch / english / italian
operating temperatur min.:	0°C
operating temperatur max.:	50°C
warranty:	24 Monate / 24 months

Link correlati a "R17IP7T-OFM1_PME"

- Avete domande relative a questo prodotto?
- Ulteriori prodotti di TL Electronic, Bergkirchen-Feldgeding

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de

Download disponibili:

Download Drawing Panel-PC R17IP7T-OFM1_PME (Panelmount) 261001.pdf

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de