


Numero Ordine: 51200417

Campo testo libero 2: 12,1 Zoll (4:3) Multitouch-Monitor

Produttore: Winmate

R12L100-GSM2

Prezzo su richiesta

 Prezzi più IVA [più spese di spedizione](#)

Tempi di consegna: su richiesta

Informazione prodotto "R12L100-GSM2"

Rugged industrial LCD for stationary and vehicle-mounted use Industrial monitor in sturdy steel sheet housing Protection class IP65 all around incl. Interfaces Shock and vibration resistant acc. MIL-STD-810F/G Flat PCAP glass front without dirt-collecting edges Designed for industrial applications in continuous operation Easy installation with rear VESA mounting interface Long-term availability

article group specification:	512
Manufacturer:	WM
Manufacturer:	Winnate
series name:	GS-Serie
Manufacturer item number:	R12L100-GSM2
mechanics:	Chassis (VESA-Mounting)
dimensions width:	29,62
dimensions height:	22,67
dimensions depth:	4,55
protection front:	IP65
protection device:	IP65
colour:	schwarz, grau / black, grey
controls:	2 Keys: Power, Reset, Status-LEDs
VESA-Mounting Interface:	VESA 75 x 75 mm
mounting:	Tragarm-, Standfuß-, Wandmontage / Suppo
Display-diagonal (inch):	12,1
aspect ratio:	4:3
resolution:	1024 x 768
brightness:	500 cd/m²
contrast:	1000:1
Display-Technology:	LCD, LED Backlight
Touch-Screen or glass:	Projected Capacitive / Multi-Touch

Touch Interface:	USB
Manufacturer controller:	P-CAP Touchcontroller
voltage input DC:	9-36 V/DC (M12 type)
external power supply:	12 V/DC, 100 - 240 V/AC, IP65
input:	18 Watt
VGA:	1 x 12-pin (M12 type)
USB:	1 x USB 2.0 (M12 type)
operating temperatur min.:	-15°C
operating temperatur max.:	55°C
warranty:	24 Monate / 24 months

Link correlati a "R12L100-GSM2"

- [- Avete domande relative a questo prodotto?](#)
- [- Ulteriori prodotti di Winmate](#)

Download disponibili:

- [Download CE Konformitätserklärung DoC LCD WM 12-Vu-x-y-z_20190130](#)
- [Download CE Industrie-LCD WM-Serie Gebrauchsanleitung 20190130](#)
- [Download Drawing Industrie-LCD WM R12L100-GSM2 221219](#)