

Numero Ordine: 23120417
Campo testo libero 2: 12.1 Zoll (4:3) Rugged Panel-PC der GS-Serie, Cortex A9, Android 6.0
Produttore: Winmate

R12FA3S-GSM2

Prezzo su richiesta

Prezzi più IVA più spese di spedizione

Tempi di consegna: su richiesta

Informazione prodotto "R12FA3S-GSM2"

Rugged Panel PC for stationary and vehicle-mounted use Industrial Panel PC in sturdy steel sheet housing Protection class IP65 all around incl. Interfaces Shock and vibration resistant acc. MIL-STD-810F/G Flat PCAP glass front without dirt-collecting edges Designed for industrial applications in continuous operation Easy installation with rear VESA mounting interface Long-term availability

article group specification:	2312
Manufacturer:	WM
Matchcode manufacturer:	nein
Manufacturer:	Winmate
series name:	GS-Serie
Manufacturer item number:	R12FA3S-GSM2
mechanics:	Chassis (VESA-Mounting)
dimensions width:	22,67
dimensions height:	29,62
dimensions depth:	4,55
Material housing:	Stahlblech / steel sheet
Material Front :	Stahlblech / steel sheet
protection front:	IP65
protection device:	IP65
colour:	schwarz / black
controls:	2 Keys: Power, Reset, Status-LEDs
VESA-Mounting Interface:	VESA 75 x 75 mm
mounting:	Tragarm-, Standfuß-, Wandmontage / Suppo
cooling:	lüfterlos / fanless
Display-diagonal (inch):	12,1
aspect ratio:	4:3
resolution:	1024 x 768

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de

brightness:	500 cd/m²
contrast:	1000:1
Display-Technologie:	LCD, LED Backlight
Touch-Screen or glass:	Projected Capactive / Multi-Touch
Touch Interface:	USB
Manufacturer controller:	P-CAP Touchcontroller
voltage input DC:	12 V/DC (M12 type)
external power supply:	12 V/DC, 100 - 240 V/AC, IP65
input:	15 Watt
USB:	1 x USB 2.0 (M12 type), 1 x USB OTG
serial:	1 x RS232 (M12 type) (Optional 422/485)
Audio:	1 x 1 Watt Speaker
LAN:	1x RJ45 - 10/100/1000 Mbps (M12 type)
Mainboard form factor:	i. MX6
chipset:	SoC
CPU Typ:	A9
CPU Model:	Cortex A9
CPU 64bit:	Nein
CPU speed:	1,0 GHz
CPU cores:	2
RAM size (MB):	1024
RAM max. size (MB):	2048
RAM Number of benches:	1
RAM Typ:	LPDDR3
Grafik Controller:	Graphics in CPU
SSD design:	eMMC
SSD max. number:	1
SSD capacity (GB):	16
Ethernet connections:	1 x RJ-45
Ethernet data transfer:	1 x Gigabit-LAN
Betriebssystem:	Android 6.0
operating-system language version:	deutsch / english / italian
operating-system support:	Linux 4.1.15, QT 5.5, Ubuntu 16.04
operating temperatur min.:	-15°C
operating temperatur max.:	55°C
warranty:	24 Monate / 24 months

Link correlati a "R12FA3S-GSM2"

- Avete domande relative a questo prodotto?
- Ulteriori prodotti di Winmate

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de

Download disponibili:

Download Drawing Panel-PC R12FA3S-GSM2 221215

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de