

Numero Ordine: 23152363
Campo testo libero 2: 15,0 Zoll (4:3) Multitouch-Panel-PC der MTU-Serie, Intel Celeron N2930
Produttore: TL Electronic
Peso:6 kg

R15IB7T-PPC3

Prezzo su richiesta

Prezzi più IVA più spese di spedizione

Tempi di consegna: su richiesta

Informazione prodotto "R15IB7T-PPC3"

Multitouch Panel PC for professional use Industrial Panel PC in sturdy steel sheet design Robust aluminium front panel (IP65 protected) Flat PCAP glass front without dirt-collecting edges Designed for industrial applications in continuous operation Panelmount installation with rear holding clamps or female screw threads Long-term availability

article group specification:	2315
Manufacturer:	WM
Matchcode manufacturer:	nein
Manufacturer:	Winmate
series name:	MTU-Serie
Manufacturer item number:	R15IB7T-PPC3
mechanics:	Panel Mount
dimensions width:	36,7
dimensions height:	29,1
dimensions depth:	8,38
Material housing:	Stahlblech / steel sheet
Material Front :	Aluminium / aluminum
protection front:	IP65
protection device:	IP20
colour:	Aluminium eloxiert / anodized aluminum
controls:	2 Keys: Power, Reset, Status-LEDs
VESA-Mounting Interface:	VESA 75 x 75 mm, 100 x 100 mm
mounting:	Einbau von vorne / front installation
cooling:	lüfterlos / fanless
Display-diagonal (inch):	15,0
aspect ratio:	4:3
resolution:	1024 x 768

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de

brightness:	300 cd/m²
contrast:	2000:1
Display-Technologie:	LCD, LED Backlight
Touch-Screen or glass:	Projected Capactive / Multi-Touch
Touch Interface:	USB
Manufacturer controller:	P-CAP Touchcontroller
voltage input DC:	12 V/DC
external power supply:	12 V/DC, 110 - 240 V/AC, 4-pin
VGA:	1 x 15-pin D-sub
USB:	1 x USB 3.0, 3 x USB 2.0
serial:	2 x RS-232, 1 x RS232/422/485
Audio:	Line-Out, Line-In, Mic in
LAN:	2x RJ45 - 10/100/1000 Mbps
PS/2:	2x Mini-DIN
Mainboard form factor:	All in One
chipset:	Intel System on chip
CPU Typ:	Celeron Bay Trail-M
CPU Model:	N2930
CPU 64bit:	Ja
CPU speed:	1,83 GHz
CPU cores:	4
CPU socket:	FCBGA1170
RAM size (MB):	4096
RAM max. size (MB):	8192
RAM Number of benches:	1
RAM Typ:	SO-DDR3L
RAM speed:	1600
Grafik Controller:	Intel HD Graphics Z3700 series
Audio Controller:	Realtek ALC886 HD Codec
safety:	TPM 2.0
SSD design:	mSATA
SSD max. number:	1
SSD capacity (GB):	128
Ethernet connections:	2 x RJ-45
Ethernet data transfer:	2 x Gigabit-LAN
Ethernet Controller :	Intel I210-AT
MiniPCIe Slot WLAN/WWAN :	2
WLAN :	Optional / optional
Betriebssystem:	Optional
operating-system language version:	deutsch / english / italian
operating-system support:	Windows 10 IoT
operating temperatur min.:	0°C

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de

operating temperatur max.:	50°C
warranty:	24 Monate / 24 months

Link correlati a "R15IB7T-PPC3"

- Avete domande relative a questo prodotto?
- Ulteriori prodotti di TL Electronic

Download disponibili:

Download WM PCAP Multi-Touch User Guide v.1.0 190228
Download Drawing Panel-PC R15IB7T-PPC3 221213

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de