



Numero Ordine: 51000317

Campo testo libero 2: 10,4 Zoll (4:3) LCD-Industriemonitor

Produttore: Winmate

R10L600-PMP1

Prezzo su richiesta

Prezzi più IVA [più spese di spedizione](#)

Tempi di consegna: su richiesta

Informazione prodotto "R10L600-PMP1"

Industrial LCD for professional use Industrial monitor in sturdy steel sheet design Robust aluminium front panel Designed for industrial applications in continuous operation Panelmount installation with rear screwed bolts Long-term availability 10,4" active Matrix TFT LCD with Aluminium-Front Panel-Mount, "Type PMA", Color black, Panel-Mount installation with rear screwed bolts Dimensions LCD: 260 x 215 x 38 mm, Dimensions Frontplate: 260 x 234 x 6 mm Resolution: 800 x 600 Pixels Contrast: 400:1 Brightness: 600 cd/m² Viewing angle: Hor.: -70° bis 70°, Vert.: -70° bis 60° Video input: 15 pin HD Sub Buchse (VGA) Power input: 12 V/DC, incl. external Power supply with 100-240 V/AC Temperature: 0-50° C (Operating), -10-60° C (Storage) incl. resistive PREMIER-Touchscreen, RS232 Type: R10L600-PMP1 (old name: WM 10-V-PMA-PRS) Country of Origin: Taiwan

article group specification:	510
Manufacturer:	WM
Manufacturer:	Winnate
series name:	WM-Serie
Manufacturer item number:	R10L600-PMP1
mechanics:	Panel Mount
dimensions width:	28,4
dimensions height:	23,4
dimensions depth:	4,3
Material Front :	Aluminium / aluminum
protection device:	IP20
colour:	RAL 9004 / signal black
controls:	5 Keys: -, +, Power, Esc, Enter
VESA-Mounting Interface:	VESA 75 x 75 mm
mounting:	Einbau von vorne / front installation
Display-diagonal (inch):	10,4
aspect ratio:	4:3
resolution:	800 x 600
brightness:	600 cd/m²

contrast:	400:1
Display-Technology:	LCD, LED Backlight
Touch-Screen or glass:	Resistive / Glas (optional)
Touch Interface:	USB oder RS-232
Manufacturer controller:	Premier
voltage input DC:	12 V/DC
voltage input AC:	100 - 240 V/AC
external power supply:	12 V/DC, 100 - 240 V/AC, DC plug
input:	15 Watt
VGA:	1 x 15-pin D-sub
DVI:	1x DVI-D (optional)
HDMI:	1 x HDMI (optional)
Video:	1 x Composite (optional)
Audio:	1 x Line-in (3,5 mm), 2 x Speaker
operating temperatur min.:	0°C
operating temperatur max.:	50°C
warranty:	24 Monate / 24 months
IstPKArtikel:	nein

Link correlati a "R10L600-PMP1"

- [- Avete domande relative a questo prodotto?](#)
- [- Ulteriori prodotti di Winmate](#)

Download disponibili:

- [Download WM Industrial LCD Monitor User Guide V11](#)
- [Download CE Industrie-LCD WM-Serie Gebrauchsanleitung 20190130](#)
- [Download CE Konformitätserklärung DoC LCD WM 10-Vu-x-y-z 20190130](#)