



**Numero Ordine:** 23152400

**Campo testo libero 2:** 15,0 Zoll (4:3) Panel-PC, Intel Pentium N4200

**Produttore:** TL Electronic, Bergkirchen-Feldgeding

## R15IP7T-OFC3\_PMA

### Prezzo su richiesta

Prezzi più IVA [più spese di spedizione](#)

Tempi di consegna: su richiesta

### Informazione prodotto "R15IP7T-OFC3\_PMA"

Built-in Panel PC for professional use Industrial Panel PC in sturdy steel sheet design Robust aluminium front panel (IP65 protected) Designed for industrial applications in continuous operation Panelmount installation with rear screwed bolts Long-term availability

|                              |                                       |
|------------------------------|---------------------------------------|
| article group specification: | 2315                                  |
| Manufacturer:                | WM                                    |
| Matchcode manufacturer:      | nein                                  |
| Manufacturer:                | Winmate                               |
| series name:                 | SlimLine-Serie                        |
| Manufacturer item number:    | R15IP7T-OFC3                          |
| mechanics:                   | Panel Mount                           |
| dimensions width:            | 41                                    |
| dimensions height:           | 34                                    |
| dimensions depth:            | 7,3                                   |
| Material housing:            | Stahlblech / steel sheet              |
| Material Front :             | Aluminium / aluminum                  |
| protection front:            | IP65                                  |
| protection device:           | IP20                                  |
| colour:                      | RAL 7035 / light grey                 |
| controls:                    | 2 Keys: Power, Reset                  |
| VESA-Mounting Interface:     | VESA 75 x 75 mm, 100 x 100 mm         |
| mounting:                    | Einbau von vorne / front installation |
| cooling:                     | lüfterlos / fanless                   |
| Display-diagonal (inch):     | 15,0                                  |
| aspect ratio:                | 4:3                                   |
| resolution:                  | 1024 x 768                            |

|                                    |                                |
|------------------------------------|--------------------------------|
| brightness:                        | 250 cd/m²                      |
| contrast:                          | 500:1                          |
| Display-Technologie:               | LCD, LED Backlight             |
| Touch-Screen or glass:             | Resistive / Glas (optional)    |
| Touch Interface:                   | USB oder RS-232                |
| Manufacturer controller:           | Premier                        |
| voltage input DC:                  | 12 V/DC                        |
| external power supply:             | 12 V/DC, 100 - 240 V/AC, 4-pin |
| VGA:                               | 1 x 15-pin D-sub (optional)    |
| HDMI:                              | 1 x HDMI 1.4 (optional)        |
| DisplayPort:                       | 1 x DisplayPort                |
| USB:                               | 4 x USB 3.0                    |
| serial:                            | 1 x RS-232/422/485             |
| Audio:                             | Mic-In, Line-Out               |
| LAN:                               | 2x RJ45 - 10/100/1000 Mbps     |
| Mainboard form factor:             | Mini-ITX                       |
| chipset:                           | Intel System on chip           |
| CPU Typ:                           | Pentium                        |
| CPU Model:                         | N4200                          |
| CPU 64bit:                         | Ja                             |
| CPU speed:                         | 1,1 GHz                        |
| CPU cores:                         | 4                              |
| CPU socket:                        | FCBGA1296                      |
| RAM size (MB):                     | 8192                           |
| RAM Number of benches:             | 2                              |
| RAM Typ:                           | SO-DDR3L                       |
| RAM speed:                         | 1866                           |
| Grafik Controller:                 | Intel HD Graphics 505          |
| Audio Controller:                  | Realtek ALC886 HD Codec        |
| safety:                            | TPM 2.0                        |
| CPU class:                         | Pentium                        |
| HDD max. number:                   | 1                              |
| HDD connection:                    | SATA                           |
| HDD capacity (GB):                 | 500                            |
| Ethernet connections:              | 2 x RJ-45                      |
| Ethernet data transfer:            | 2 x Gigabit-LAN                |
| Ethernet Controller :              | 2x Intel I210-AT               |
| MiniPCle Slot WLAN/WWAN :          | 1                              |
| Betriebssystem:                    | Optional                       |
| operating-system language version: | deutsch / english / italian    |
| operating-system support:          | Windows 10 IoT                 |
| operating temperatur min.:         | 0°C                            |

operating temperatur max.:

50°C

warranty:

24 Monate / 24 months

**Link correlati a "R15IP7T-OFC3\_PMA"**

- [- Avete domande relative a questo prodotto?](#)
- [- Ulteriori prodotti di TL Electronic, Bergkirchen-Feldgeding](#)

**Download disponibili:**

- [Download Drawing Panel-PC WM 15-...-PMA+PME \(Panelmount\) 190228](#)
- [Download CE Konformitätserklärung DoC Panel-PC WM 15-IP70-x-y-z](#)