

**Numero Ordine:** 15000584
**Campo testo libero 2:** Wallmount Industrie-PC der EmbeddedLine-Serie, Intel Core i5-1145GRE
**Produttore:** Protech
**Peso:**3.2 kg

# IV-Z318

## Prezzo su richiesta

Prezzi più IVA più spese di spedizione

Tempi di consegna: su richiesta

### Informazione prodotto "IV-Z318"

Booksize Embedded PC for professional use Industrial computer in sturdy aluminium housing Designed for industrial applications in continuous operation Easy installation with mounting bars or DIN Rail kit Long-term availability

| | |
|---|---|
| **article group specification:** | 150 |
| **Manufacturer:** | PT |
| **Matchcode manufacturer:** | nein |
| **Manufacturer:** | Protech |
| **series name:** | EmbeddedLine |
| **Manufacturer item number:** | IV-Z318 |
| **mechanics:** | Embedded-PC |
| **dimensions width:** | 25,95 |
| **dimensions height:** | 7,2 |
| **dimensions depth:** | 18,48 |
| **weight:** | 3,2 |
| **Material housing:** | Aluminium / aluminium |
| **Material Front :** | Aluminium / aluminum |
| **protection front:** | IP20 |
| **protection device:** | IP20 |
| **colour:** | schwarz / black |
| **VESA-Mounting Interface:** | VESA 75 x 75 mm |
| **wall mounting:** | Ja / yes |
| **cooling:** | lüfterlos / fanless |
| **DIN-Rail:** | Optional / optional |
| **chipset:** | Intel System on chip |
| **CPU Typ :** | Core i5 |

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de

| | |
|---|---|
| **CPU Model :** | 1145GRE |
| **CPU 64bit :** | Ja |
| **CPU speed:** | 1,50 GHz |
| **CPU cores:** | 4 |
| **CPU socket:** | FCBGA1449 |
| **CPU alternative option 1:** | Core i3-1115GRE |
| **CPU alternative option 2:** | Core i7-1185GRE |
| **RAM size (MB):** | 8192 |
| **RAM max. size (MB):** | 32768 |
| **RAM Number of benches:** | 2 |
| **RAM Typ :** | SO-DDR4 |
| **RAM speed:** | 3200 |
| **Grafik Controller:** | Intel Iris Xe Graphics |
| **safety:** | TPM 2.0 |
| **connections SATA:** | 2 |
| **Mini-PCIe-slot:** | 2 |
| **HDD design:** | 2.5" |
| **HDD max. number:** | 2 |
| **HDD connection:** | SATA |
| **MiniPCIe Slot SSD :** | 3 |
| **SSD design:** | M.2 |
| **SSD max. number:** | 1 |
| **SSD capacity (GB):** | 256 |
| **RAID-System :** | Ja / yes |
| **SIM Card Slot :** | Ja / yes |
| **Display :** | 2x HDMI 2.0, 1x DP 1.4 |
| **USB :** | 2x USB 3.2, 2 x USB 2.0 |
| **LAN :** | 4x RJ45 - 10/100/1000 Mbps |
| **Audio :** | Mic-In |
| **serial:** | 2 x RS-232, 2 x RS232/422/485 |
| **Digitale I/O :** | 1 x 4in / 4out |
| **controls:** | Power On/Off, Reset |
| **voltage input DC:** | 9-48 V/DC |
| **operating-system support:** | Windows 10 IoT / Ubuntu 20.14 |
| **operating temperatur min.:** | -40°C |
| **operating temperatur min.:** | 70°C |
| **warranty:** | 24 Monate / 24 months |

## Link correlati a "IV-Z318"

- Avete domande relative a questo prodotto?
- Ulteriori prodotti di Protech

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de

## Download disponibili:

Download Drawing Embedded-Industrie-PC IV-Z318 230721.pdf

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de