


Numero Ordine: 23100491

Campo testo libero 1: -1

Campo testo libero 2: 10,1 Zoll (16:10) Rugged Industrie-Tablet-

Produttore: Winmate

Peso: 1 kg

M101M8

Prezzo su richiesta

 Prezzi più IVA [più spese di spedizione](#)

 Pronto per la spedizione di oggi,
 tempo di consegna ca. 1-3 giorni lavorativi

Informazione prodotto "M101M8"

Tablet PC for professional use Ruggedized Tablet in sturdy aluminium housing Protection class IP65 all around incl. Interfaces Shock, vibration and drop protected (MIL-STD-810G) Multi-touch (PCAP) with Glove / Rain / Stylus modes Wide range of options and accessories for data capture, communication, docking, mounting, power, peripherals and transportation The ideal partner for warehouse, logistics, automotive, outdoor, smart factory, field service etc.

article group specification:	2310
Manufacturer:	WM
Matchcode manufacturer:	nein
Manufacturer:	Winnate
series name:	Rugged Industrial Tablet PC
Manufacturer item number:	M101M8
mechanics:	Rugged Tablet PC
dimensions width:	27,18
dimensions height:	19,72
dimensions depth:	1,9
weight:	1,0
Material housing:	Aluminium - Magnesium
protection device:	IP65
colour:	Schwarz / black
cooling:	l�fterlos / fanless
Display-diagonal (inch):	10,1
aspect ratio:	16:10
resolution:	1280 x 800
brightness:	300 cd/m�
contrast:	1000:1

Display-Technology:	LCD, LED Backlight
Touch-Screen :	Projected Capacitive / Multi-Touch
usability:	Finger/Stift/Handschuh / finger/pen/glov
CPU Typ:	ARM Cortex
CPU Model:	A53
CPU speed:	1,3 GHz
CPU cores:	8
RAM size (MB):	2048
RAM Typ:	LPDDR3
SSD design:	mSATA
SSD capacity:	16
SSD number:	1
SSD number max.:	1
safety:	Kensington lock
WLAN:	Ja / yes
WLAN-Standard:	IEEE 802.11 a/b/g/n
Bluetooth:	Ja / yes
WWAN:	Ja / yes
Camera front:	Ja / yes
Camera front resolution:	2MP
Camera rear:	Ja / yes
Camera rear resolution:	8MP
Barcode:	2D Barcode-Reader
Video:	1x Mirco HDMI
USB:	1x USB 2.0
Card Slot:	1x Micro SD Slot
Audio:	1x Audio Combo Conn.(Mic in/Line out)
Docking connector:	1x 19-pin Docking Connector
controls:	5 Keys: 1x Power, 2x Volume, 2x Function
operating system:	Android 5.1
operating temperatur min.:	-10°C
operating temperatur max.:	50°C
Shock:	MIL-STD-810G Method 516.6 Procedure I
Vibration:	MIL-STD-810G Method 514.6 Procedure I
Drop:	MIL-STD-810G Method 516.6, 4 ft
voltage input DC:	12 V/DC
external power supply:	12 V/DC, 100 - 240 V/AC, DC plug
battery:	7.4V, 5140 mAh (typ.) Li-Polymer Battery
battery Hot-Swap:	Ja / yes

Link correlati a "M101M8"

[- Avete domande relative a questo prodotto?](#)

[- Ulteriori prodotti di Winmate](#)

Download disponibili:

[Download CE Konformitätserklärung DoC Tablet-PC M101M8_20190130](#)

[Download Drawing Tablet-PC M101M8 190228](#)