


**Numero Ordine:** 23100602

**Campo testo libero 2:** 10,4 Zoll (16:9) Panel-PC, Intel Celeron N2930

**Produttore:** Winmate

## R10IB3S-GCT2

### Prezzo su richiesta

 Prezzi più IVA [più spese di spedizione](#)

Tempi di consegna: su richiesta

### Informazione prodotto "R10IB3S-GCT2"

Built-in Panel PC for professional use Industrial Panel PC in sturdy steel sheet design Robust plastic front panel (IP65 protected) Shock and vibration resistant acc. MIL-STD-810F/G Designed for industrial applications in continuous operation Panelmount installation with rear screwed bolts Long-term availability

|                              |                                          |
|------------------------------|------------------------------------------|
| article group specification: | 2310                                     |
| Manufacturer:                | WM                                       |
| Matchcode manufacturer:      | nein                                     |
| Manufacturer:                | Winnate                                  |
| series name:                 | GC-Serie                                 |
| Manufacturer item number:    | R10IB3S-GCT2                             |
| mechanics:                   | Chassis (VESA-Mounting)                  |
| dimensions width:            | 25,24                                    |
| dimensions height:           | 19,78                                    |
| dimensions depth:            | 4,14                                     |
| Material housing:            | Stahlblech / steel sheet                 |
| Material Front :             | Kunststoff / plastic                     |
| protection front:            | IP65                                     |
| colour:                      | schwarz / black                          |
| controls:                    | 2 Keys: Power, Reset                     |
| VESA-Mounting Interface:     | VESA 75 x 75 mm, 100 x 100 mm            |
| mounting:                    | Tragarm-, Standfuß-, Wandmontage / Suppo |
| cooling:                     | lufferlos / fanless                      |
| Display-diagonal (inch):     | 10,4                                     |
| aspect ratio:                | 4:3                                      |
| resolution:                  | 1024 x 768                               |
| brightness:                  | 350 cd/m²                                |

|                                    |                                       |
|------------------------------------|---------------------------------------|
| contrast:                          | 1000:1                                |
| Display-Technologie:               | LCD, LED Backlight                    |
| Touch-Screen or glass:             | Projected Capacitive / Multi-Touch    |
| Touch Interface:                   | USB                                   |
| Manufacturer controller:           | P-CAP Touchcontroller                 |
| voltage input DC:                  | 12 V/DC                               |
| external power supply:             | 12 V/DC, 100 - 240 V/AC, 4-pin        |
| HDMI:                              | 1 x HDMI (optional)                   |
| USB:                               | 1 x USB 3.0, 1 x USB 2.0              |
| serial:                            | 1 x RS-232                            |
| LAN:                               | 2x RJ45 - 10/100/1000 Mbps            |
| CPU Typ:                           | Celeron                               |
| CPU Model:                         | N2930                                 |
| CPU 64bit:                         | Ja                                    |
| CPU speed:                         | 1,83 GHz                              |
| CPU cores:                         | 4                                     |
| CPU socket:                        | FCBGA1170                             |
| RAM size (MB):                     | 4096                                  |
| RAM Number of benches:             | 1                                     |
| RAM Typ:                           | SO-DDR3L                              |
| RAM speed:                         | 1600                                  |
| Grafik Controller:                 | Intel HD Graphics Z3700 series        |
| safety:                            | TPM 2.0                               |
| CPU class:                         | Atom / Celeron                        |
| SSD design:                        | M.2                                   |
| SSD max. number:                   | 1                                     |
| SSD capacity (GB):                 | 128                                   |
| Ethernet connections:              | 2 x RJ-45                             |
| Ethernet data transfer:            | 2 x Gigabit-LAN                       |
| Ethernet Controller :              | 2 x Intel Gigabit Ethernet Controller |
| WLAN :                             | Optional / optional                   |
| Bluetooth :                        | optional / optional                   |
| Betriebssystem:                    | Optional                              |
| operating-system language version: | deutsch / english / italian           |
| operating temperatur min.:         | 0°C                                   |
| operating temperatur max.:         | 50°C                                  |
| warranty:                          | 24 Monate / 24 months                 |

## Link correlati a "R10IB3S-GCT2"

- [- Avete domande relative a questo prodotto?](#)
- [- Ulteriori prodotti di Winmate](#)

**Download disponibili:**[Download Drawing Panel-PC R10IB3S-GCT2\\_12092022](#)[Download CE Konformitätserklärung DoC W10IB3S-GCH2](#)