Numero Ordine: 25110016
Campo testo libero 2: 11,6 Zoll (16:9) Rugged Industrie-Tablet-PC, Intel Pentium N4200, Windows 10 IoT Enterprise
Produttore: Winmate
Peso:1.45 kg

M116PT

Prezzo su richiesta

Prezzi più IVA più spese di spedizione

Tempi di consegna: su richiesta

Informazione prodotto "M116PT"

Tablet PC for professional use Ruggedized Tablet in sturdy aluminium housing Protection class IP65 all around incl. Interfaces Shock, vibration and drop protected (MIL-STD-810G) Multi-touch (PCAP) with Glove / Rain / Stylus modes Wide range of options and accessories for data capture, communication, docking, mounting, power, peripherals and transportation The ideal partner for warehouse, logistics, automotive, outdoor, smart factory, field service etc.

article group specification:	2511
Manufacturer:	WM
Matchcode manufacturer:	nein
Manufacturer:	Winmate
series name:	Rugged Industrial Tablet PC
Manufacturer item number:	M116PT
mechanics:	Rugged Tablet PC
dimensions width:	30,1
dimensions height:	20,2
dimensions depth:	2,25
weight:	1,45
Material housing:	Aluminium - Magnesium
protection device:	IP65
colour:	Schwarz / black
cooling:	lüfterlos / fanless
Display-diagonal (inch):	11,6
aspect ratio:	16:9
resolution:	1920 x 1080
brightness:	850 cd/m²
contrast:	1000:1
Display-Technology:	LCD, LED Backlight

Touch-Screen :	Projected Capactive / Multi-Touch
usability:	Finger/Stift/Handschuh / finger/pen/glov
CPU Typ:	Pentium
CPU Model:	N4200
CPU speed:	1,1 GHz
CPU cores:	4
RAM size (MB):	4096
RAM Typ:	LPDDR4
SSD capacity:	128
SSD number:	1
WLAN:	Optional / optional
Bluetooth:	Optional / optional
WWAN:	Optional / optional
Ethernet_connections:	1x RJ-45
Ethernet data transfer:	1 x Gigabit-LAN
Camera front:	Ja / yes
Camera front resolution:	2MP
Camera rear:	Ja / yes
Camera rear resolution:	8MP
RFID:	Optional / optional
Video:	1x Mirco HDMI (optional)
USB:	1x USB 3.0 (Type A), 1x USB 3.0 (Type C)
Card Slot:	1x Micro SDXC Slot, 1x Micro SIM Slot
Audio:	1x Line-in / Line-out (3,5 mm)
Power:	1x 19 V/DC, DC plug
Docking connector:	1x 19-pin Docking Connector
controls:	4 Keys: Power, Volume, Fn1, Fn2
operating system:	Windows 10 IoT Enterprise
operating temperatur min.:	-10°C
operating temperatur max.:	50°C
Shock:	MIL-STD-810G Method 516.6 Procedure I
Vibration:	MIL-STD-810G Method 514.6 Procedure I
Drop:	MIL-STD-810G Method 516.6, 4 ft
voltage input DC:	19 V/DC
external power supply:	19 V/DC, 100 - 240 V/AC, DC plug
battery:	7.7V, 5900 mAh Li-Polymer Battery (2S1P)
battery Hot-Swap:	Ja / yes

Link correlati a "M116PT"

- Avete domande relative a questo prodotto?
- Ulteriori prodotti di Winmate

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de

Download disponibili:

Download Drawing Tablet-PC M116PT_12092022
Download CE Konformitätserklärung DoC Tablet-PC M116PT_28092022

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de