

Numero Ordine: 23100555
Campo testo libero 2: 10,4 Zoll (4:3) Edelstahl-Panel-PC, Intel Celeron N2930
Produttore: Winmate
Peso:5 kg

R10IB3S-SPT2

Prezzo su richiesta

Prezzi più IVA più spese di spedizione

Tempi di consegna: su richiesta

Informazione prodotto "R10IB3S-SPT2"

Widerstandsfähiger Industrie-Panel-PC aus gebürstetem Edelstahl
Schutzart IP65 rundum inkl. Schnittstellen
Leicht zu reinigen und korrosionsbeständig
Ausgelegt für industrielle Anwendungen im Dauerbetrieb
Einfache Installation mit rückseitiger VESA-Montageschnittstelle
Perfekt für Lebensmittel-, Chemie-, Pharmaindustrie, Medizintechnik, Verfahrenstechnik, Anlagenbau etc.

article group specification:	2310
Manufacturer:	WM
Matchcode manufacturer:	nein
Manufacturer:	Winmate
series name:	ES-Serie
Manufacturer item number:	R10IB3S-SPT2
mechanics:	Chassis Edelstahl / stainless steel (VES
dimensions width:	28,9
dimensions height:	24,6
dimensions depth:	4,99
weight:	5,0
Material housing:	Edelstahl / stainless steel
Material Front :	Edelstahl / stainless steel
protection front:	IP65
protection device:	IP65
colour:	Edelstahl gebürstet / brushed stainless
controls:	2 Keys: Power, Reset
VESA-Mounting Interface:	VESA 75 x 75 mm
mounting:	Tragarm-, Standfuß-, Wandmontage / Suppo
cooling:	lüfterlos / fanless

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de

Display-diagonal (inch):	10,4
aspect ratio:	4:3
resolution:	1024 x 768
brightness:	350 cd/m²
contrast:	1000:1
Display-Technologie:	LCD, LED Backlight
Touch-Screen or glass:	Projected Capactive / Multi-Touch
Touch Interface:	USB
Manufacturer controller:	P-CAP Touchcontroller
voltage input DC:	12 V/DC (M12 type)
external power supply:	12 V/DC, 100 - 240 V/AC, 4-pin
USB:	2 x USB 2.0 (M12 type)
serial:	1 x RS-232 (M12 type)
LAN:	1x RJ45 - 10/100/1000 Mbps (M12 type)
chipset:	Intel System on chip
CPU Typ:	Celeron
CPU Model:	N2930
CPU 64bit:	Ja
CPU speed:	1,83 GHz
CPU cores:	4
CPU socket:	FCBGA1170
RAM size (MB):	4096
RAM Number of benches:	1
RAM Typ:	SO-DDR3L
RAM speed:	1600
Grafik Controller:	Intel HD Graphics Z3700 series
CPU class:	Atom / Celeron
SSD design:	mSATA
SSD max. number:	1
SSD capacity (GB):	64
Ethernet connections:	1 x RJ-45
Ethernet data transfer:	1 x Gigabit-LAN
operating temperatur min.:	0°C
operating temperatur max.:	45°C
warranty:	24 Monate / 24 months

Link correlati a "R10IB3S-SPT2"

- Avete domande relative a questo prodotto?
- Ulteriori prodotti di Winmate

Download disponibili:

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de

Download Drawing Panel-PC R10IB3S-SPT2 190228
Download CE Konformitätserklärung DoC Panel-PC R10IB3S-SPT2

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de