

Numero Ordine: 23070040
Campo testo libero 2: 7,0 Zoll (16:9) Vehicle Mount Computer VMC Serie, Cortex A53, Android 11
Produttore: Winmate
Peso:1.25 kg

FM07M

Prezzo su richiesta

Prezzi più IVA più spese di spedizione

Tempi di consegna: su richiesta

Informazione prodotto "FM07M"

Tablet PC ready for vehicle and forklift installation Ruggedized Tablet and docking unit in sturdy magnesium alloy housing Protection class IP65 all around incl. Interfaces Shock and vibration protected (MIL-STD-810H) Antiscratch resistive touch (finger & stylus) The ideal partner for warehouse, logistics, automotive, outdoor etc. Long-term availability

article group specification:	2307
Manufacturer:	WM
Matchcode manufacturer:	nein
Manufacturer:	Winmate
series name:	Vehicle Mounted Computer
Manufacturer item number:	FM07M
mechanics:	Vehicle Mount Computer
dimensions width:	19,0
dimensions height:	14,6
dimensions depth:	4,0
weight:	1,25
Material housing:	Aluminium / aluminium
protection device:	IP65
colour:	Schwarz / black
VESA-Mounting Interface:	VESA 75 x 75 / 30,5 x 38,1
cooling:	lüfterlos / fanless
Display-diagonal (inch):	7,0
aspect ratio:	16:9
resolution:	1024 x 600
brightness:	1000 cd/m²
contrast:	700:1
Display-Technology:	LCD, LED Backlight

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de

Touch-Screen :	Projected Capactive / Multi-Touch
usability:	Finger/Stift / finger/pen
CPU Typ:	ARM Cortex
CPU Model:	A53
CPU speed:	2,0 GHz
RAM size (MB):	4096
RAM Typ:	LPDDR4
SSD design:	eMMC
SSD capacity:	32
SSD number:	1
safety:	TPM 2.0
WLAN:	Ja / yes
Bluetooth:	Ja / yes
WWAN:	Optional / optional
Ethernet_connections:	1x RJ-45
Ethernet data transfer:	1 x Gigabit-LAN
USB:	2x USB for DB9, 1x USB Micro OTG
serial:	1x RS-232
LAN:	1x RJ45 - 10/100 Mbps
Card Slot:	1x SD Slot, 1x SIM Slot (optional)
Audio:	1 x Speaker
Power:	1x 9-24 V/DC, DC plug
controls:	6 Keys: Power, 5x Function
operating system:	Android 11
operating temperatur min.:	-20°C
operating temperatur max.:	60°C
Shock:	MIL-STD-810H Method 516.6 Procedure I
Vibration:	MIL-STD-810H Method 514.8 Procedure I
voltage input DC:	12 V/DC
external power supply:	12 V/DC, 100 - 240 V/AC, DC plug

Link correlati a "FM07M"

- Avete domande relative a questo prodotto?
- Ulteriori prodotti di Winmate

Download disponibili:

Download Drawing Vehicle Mounted Computer FM07M 230216
Download CE Konformitätserklärung DoC FM07M.pdf

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de