


**Numero Ordine:** 25070008

**Campo testo libero 2:** 7,0 Zoll (16:9) ATEX Rugged-Android-PDA, Qualcomm Snapdragon 660, Android 9.0

**Produttore:** Winmate

**Peso:** 550 kg

## M700DQ8-EX

### Prezzo su richiesta

 Prezzi più IVA [più spese di spedizione](#)

Tempi di consegna: su richiesta

### Informazione prodotto "M700DQ8-EX"

7" Android Tablet, (1280 x 720) TFT Panel ATEX rugged android PDA Qualcomm® Snapdragon™ 660, Octa-core up to 2.2 GHz ATEX Zone 2 application certification Supports Android 9.0 OS Protection class IP67 all around incl. Interfaces Shock, vibration and drop protected (MIL-STD-810G) Multi-touch (PCAP) with Glove, Rain and Stylus modes Choice of various standard and optional accessories configurable

article group specification:	2507
Manufacturer:	WM
Matchcode manufacturer:	nein
Manufacturer:	Wimate
Manufacturer item number:	M700DQ8-EX
dimensions width:	13,28
dimensions height:	21,24
dimensions depth:	1,9
weight:	550
Material housing:	Magnesium Legierung / Magnesium alloy
protection device:	IP65
colour:	Schwarz / black
cooling:	lüfterlos / fanless
Display-diagonal (inch):	7,0
aspect ratio:	16:9
resolution:	1280 x 720
brightness:	650 cd/m <sup>2</sup>
contrast:	800:1
Display-Technology:	LCD, LED Backlight
Touch-Screen :	Projected Capacitive / Multi-Touch
usability:	Finger/ Handschuh/ finger/ glove
CPU Typ:	Qualcomm

<b>CPU Model:</b>	Snapdragon 660
<b>CPU speed:</b>	2,2 GHz
<b>CPU cores:</b>	8
<b>RAM size (MB):</b>	3072
<b>SSD capacity:</b>	32
<b>SSD number:</b>	1
<b>WLAN:</b>	Ja / yes
<b>Bluetooth:</b>	Ja / yes
<b>WWAN:</b>	Optional / optional
<b>Camera front:</b>	Ja / yes
<b>Camera front resolution:</b>	8MP
<b>Camera rear:</b>	Ja / yes
<b>Camera rear resolution:</b>	13MP
<b>USB:</b>	1x USB 3.0 Type C OTG
<b>Card Slot:</b>	1x Micro SD Slot, 1x Micro SIM Slot
<b>Docking connector:</b>	1x 19-pin Docking Connector
<b>controls:</b>	6 Keys: Power, 5x Function
<b>operating system:</b>	Android 9.0
<b>operating temperatur min.:</b>	-10°C
<b>operating temperatur max.:</b>	50°C
<b>Shock:</b>	MIL-STD-810G Method 516.6 Procedure I
<b>Vibration:</b>	MIL-STD-810G Method 514.6 Procedure I
<b>Drop:</b>	MIL-STD-810G Method 516.6, 5 ft
<b>voltage input DC:</b>	5 V/DC
<b>external power supply:</b>	5 V/DC, 100 - 240 V/AC, DC plug
<b>battery:</b>	3.7V 5300mAh

## Link correlati a "M700DQ8-EX"

- [- Avete domande relative a questo prodotto?](#)
- [- Ulteriori prodotti di Winmate](#)

## Download disponibili:

[Download Drawing Tablet-PC M700DQ8 221212.pdf](#)