


Numero Ordine: 25100076

Campo testo libero 2: 10,1 Zoll (16:10) Healthcare Rugged Tablet-PC, Intel Pentium N4200, Windows 10 IoT Enterprise

Produttore: Winmate

Peso: 1.2 kg

M101P

Prezzo su richiesta

 Prezzi più IVA [più spese di spedizione](#)

Tempi di consegna: su richiesta

Informazione prodotto "M101P"

10.1" (1920 x 1200) IPS LED Panel with direct optical bonding Intel® Pentium® N4200 Windows Healthcare Rugged Tablet Protection class IP65 all around incl. Interfaces Ruggedized tablet in aluminum case equipped with antimicrobial properties Choice of various standard and optional accessories configurable Shock, vibration and drop protected (MIL-STD-810G) Multi-touch (PCAP) with Glove / Rain / Stylus modes

article group specification:	2510
Manufacturer:	WM
Matchcode manufacturer:	nein
Manufacturer:	Winnate
series name:	Rugged Industrial Tablet PC
Manufacturer item number:	M101P-ME
mechanics:	Rugged Tablet PC
dimensions width:	27,19
dimensions height:	19,73
dimensions depth:	1,95
weight:	1,2
Material housing:	Aluminium - Magnesium
protection device:	IP65
colour:	weiß / white
cooling:	l�fterlos / fanless
Display-diagonal (inch):	10,1
aspect ratio:	16:9
resolution:	1920 x 1200
brightness:	650 cd/m ²
contrast:	800:1
Display-Technology:	LCD, LED Backlight
Touch-Screen :	Projected Capacitive / Multi-Touch

CPU Typ:	Pentium
CPU Model:	N4200
CPU speed:	1,1 GHz
CPU cores:	4
RAM size (MB):	4096
RAM max. Größe (MB):	8192
SSD capacity:	128
SSD number:	1
WLAN:	Ja / yes
Bluetooth:	Ja / yes
WWAN:	Optional / optional
Camera front:	Ja / yes
Camera front resolution:	2MP
Camera rear:	Ja / yes
Camera rear resolution:	8MP
Video:	1x HDMI (optional)
USB:	1x USB 3.0 (Type A), 1x USB 3.0 (Type C)
Card Slot:	1x Micro SDXC Slot, 1x Micro SIM Slot
Docking connector:	1x 19-pin Docking Connector
controls:	6 Keys: Power, 5x Function
operating system:	Windows 10 IoT Enterprise
operating temperatur min.:	0°C
operating temperatur max.:	35°C
Shock:	MIL-STD-810G Method 516.6 Procedure I
Vibration:	MIL-STD-810G Method 514.6 Procedure I
Drop:	MIL-STD-810G Method 516.6, 4 ft
voltage input DC:	19 V/DC
external power supply:	19 V/DC, 100 - 240 V/AC, DC plug
battery:	7.4V, 5140 mAh (typ.) Li-Polymer Battery
battery Hot-Swap:	Ja / yes

Link correlati a "M101P"

- [- Avete domande relative a questo prodotto?](#)
- [- Ulteriori prodotti di Winmate](#)