



**Numero Ordine:** 51701239  
**Campo testo libero 2:** 17,0 Zoll (4:3) Marine Display  
**Produttore:** Winmate

## R17L500-MRM1

### Prezzo su richiesta

Prezzi più IVA [più spese di spedizione](#)

Tempi di consegna: su richiesta

### Informazione prodotto "R17L500-MRM1"

17" (1280 x 1024) Marine Display Protection class IP66 Front side protected, IP54 Back side protected Dimming knob control backlight brightness from nearly 0% to 100% User-friendly OSD control on the front marine display Enhanced shock and vibration resistance inclusive Resistive Touchscreen Option: Anti-Reflection Protection Glass 24V DC-in with Isolation (Approval by Certificate) 9 to 36V DC Input Acceptable VESA Mount/ Panel Mount 17" Marine Display Dimming knob control backlight brightness from nearly 0% to 100% IP66 aluminum housing with powder coating design (IP54 rear) 9-36 V/DC Isolated Power Module High quality resistive touchscreen Ease of use front panel OSD control Marine Display Enhanced shock and vibration resistance Dimensions Display: 460 x 410 x 77.2 mm, Rear VESA Mounting with 100x100 mm. Resolution: 1280 x 1024 Pixel Contrast: 1000:1 Brightness: 350 cd/m<sup>2</sup> View Angle: Hor.: -85° bis 85°, Vert.: -80° bis 80° I/O Ports: 1x VGA, 1x DVI-D, 1x Composite, 1x S-Video, 1x RS-232 for remote control, Front control: ESC/PIP, Auto adjustment, Left, Right/Source, OK/Menu, UP, Down, Power, 1x The Dimming Knob. Power rating: 9-36 V/DC incl. resistive Touch Screen Operating temperature: -15~55° C (Operating) Anti-Vibration: 0.7g@DNVGL CG-0339 (Class A) Anti-Shock: 15G, 11ms duration Certifications: IEC 60945 4th, IACS E10, CE, FCC Type: R17L500- MRM1 (with res. Touch) Country of Origin: Taiwan

article group specification:	517
Manufacturer:	WM
MatchcodeHersteller:	nein
Manufacturer:	Wimate
Manufacturer item number:	R17L500-MRM1
mechanics:	Panel Mount
dimensions width:	46,0
dimensions height:	41,0
dimensions depth:	7,72
Material housing:	Stahlblech / steel sheet
Material Front :	Aluminium / aluminum
protection front:	IP66
colour:	schwarz / black
controls:	8 Keys: Power, 7x Function
VESA-Mounting Interface:	VESA 100 x 100 mm
mounting:	Einbau von vorne / front installation

Display-diagonal (inch):	17,0
aspect ratio:	4:3
resolution:	1280 x 1024
brightness:	350 cd/m <sup>2</sup>
contrast:	1000:1
Display-Technology:	LCD, LED Backlight
Touch-Screen or glass:	Resistive Touch
Touch Interface:	USB
Manufacturer controller:	Premier
voltage input DC:	9-36 V/DC
external power supply:	12 V/DC, 100 - 240 V/AC, 4-pin
VGA:	1 x 15-pin D-sub
DVI:	1 x DVI-D
Video:	1 x Composite, 1 x S-Video
serial:	2 x RS232
operating temperatur min.:	-15°C
operating temperatur max.:	55°C
warranty:	24 Monate / 24 months

## Link correlati a "R17L500-MRM1"

- [- Avete domande relative a questo prodotto?](#)
- [- Ulteriori prodotti di Winmate](#)

## Download disponibili:

[Download Drawing LCD R17L500-MRM1 13062023.pdf](#)