

Numero Ordine: 25100073
Campo testo libero 2: 10,4 Zoll (4:3) Ultra Rugged Tablet PC, Intel Core i5-8265U
Produttore: Winmate
Peso:2.4 kg

R10IWK8M-RTT2GP

Prezzo su richiesta

Prezzi più IVA più spese di spedizione

Tempi di consegna: su richiesta

Informazione prodotto "R10IWK8M-RTT2GP"

10.4" (1024 x 768) Resolution Transflective TFT-LCD Panel Intel® Core® i5 1135G7 Defence Ultra Rugged Tablet Ruggedized tablet in sturdy Magnbesium Alloy housing with all-around elastomeric rubber MIL-STD-38999 connector for LAN/USB2.0, RS232/RS422 and DC Power Input Adjustable Kickstand that is Convertible to a handle Protection class IP54 all around incl. connectors Shock, vibration and drop protected (MIL-STD-810G)

article group specification:	2510
Manufacturer:	WM
Matchcode manufacturer:	nein
Manufacturer:	Winmate
series name:	Ultra Rugged Tablet PC
Manufacturer item number:	R10IWK8M-RTT2GP
mechanics:	Ultra Rugged Tablet PC
dimensions width:	26,6
dimensions height:	22,4
dimensions depth:	5,04
weight:	2,4
Material housing:	Magnesium Legierung / Magnesium alloy
protection device:	IP54
colour:	Schwarz / black
cooling:	lüfterlos / fanless
Display-diagonal (inch):	10,4
aspect ratio:	4:3
resolution:	1024 x 768
brightness:	700 cd/m²
contrast:	1000:1
Display-Technology:	LCD, LED Backlight

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de

Touch-Screen :	Resistive Touch (optional)
CPU Typ:	Core i5
CPU Model:	8265U
CPU speed:	1,6 GHz
CPU cores:	4
RAM size (MB):	4096
RAM max. Größe (MB:	32768
RAM Typ:	SO-DDR4
RAM speed:	2400
SSD design:	M.2
SSD capacity:	128
SSD number:	1
safety:	TPM 2.0
WLAN:	Ja / yes
Bluetooth:	Ja / yes
WWAN:	Optional / optional
Ethernet_connections:	1x RJ-45
Ethernet data transfer:	1 x Gigabit-LAN
Camera front:	Optional / optional
Camera rear:	Optional / optional
Barcode:	Optional / optional
USB:	2x USB 3.2
serial:	1x RS-232
LAN:	1x RJ45 - 10/100 Mbps
Card Slot:	1x Micro SD Slot, 1x Micro SIM Slot
Audio:	1x Mic in/Line out, 2x Speaker
operating temperatur min.:	-10°C
operating temperatur max.:	50°C
Shock:	MIL-STD-810G Method 516.6 Procedure I
Vibration:	MIL-STD-810G Method 514.6 Procedure I
Drop:	MIL-STD-810G Method 516.6, 4 ft
external power supply:	19 V/DC, 110 - 240 V/AC, DC plug
battery:	11.1V, 5200 mAh Li-ion Battery

Link correlati a "R10IWK8M-RTT2GP"

- Avete domande relative a questo prodotto?
- Ulteriori prodotti di Winmate

Download disponibili:

Download Drawing Tablet-PC R10IWK8M-RTT2GP 230224

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de