



Numero Ordine: 25150001

Campo testo libero 2: 15,6 Zoll Rugged Industrial Laptop, i7-12700H, Windows 10 IoT Enterprise

Produttore: Winmate

Peso: 2.8 kg

L156AD-M1

Prezzo su richiesta

Prezzi più IVA [più spese di spedizione](#)

Tempi di consegna: su richiesta

Informazione prodotto "L156AD-M1"

Rugged Laptop for professional use Shock, vibration and drop protected (MIL-STD-810H) Multi-touch (PCAP) Wide range of options and accessories for data capture, communication, docking, mounting, power, peripherals and transportation The ideal partner for warehouse, logistics, automotive, outdoor, smart factory, field service etc. Long-term availability

article group specification:	2515
Manufacturer:	WM
Matchcode manufacturer:	nein
Manufacturer:	Wimate
series name:	Rugged Laptop
Manufacturer item number:	L156AD-M1
mechanics:	Rugged Laptop
dimensions width:	38,76
dimensions height:	3,88
dimensions depth:	25,6
weight:	2,8
protection device:	IP65
colour:	Schwarz / black
cooling:	aktiv / fan cooling
Display-diagonal (inch):	15,6
resolution:	1920 x 1080
brightness:	800 cd/m ²
contrast:	800:1
Display-Technology:	LCD, LED Backlight
Touch-Screen :	Projected Capacitive / Multi-Touch
CPU Typ:	Core i7
CPU Model:	12700H

CPU speed:	2,30 GHz
CPU cores:	14
RAM size (MB):	32768
RAM max. Größe (MB):	65536
RAM Typ:	SDRAM-DDR5
SSD design:	M.2
SSD capacity:	256
SSD number:	1
safety:	TPM 2.0
WLAN:	Ja / yes
Bluetooth:	Ja / yes
Ethernet_connections:	2x RJ-45
Ethernet data transfer:	2 x Gigabit-LAN
Camera front:	Ja / yes
Camera front resolution:	2MP
RFID:	Optional / optional
Finger Print:	Optional / optional
Video:	1x HDMI 4K (optional)
USB:	3x USB 3.0 (Type A), 1x USB 3.0 (Type C)
serial:	1x RS-232 (DB9)
LAN:	2x RJ45 - 10/100/1000 Mbps
Card Slot:	1x Micro SDXC Slot
Audio:	1x Audio Combo jack 3.5mm
Power:	1x 19 V/DC, DC plug
controls:	5 Keys: Power, 4x Function Key
operating system:	Windows 10 IoT Enterprise
operating temperatur min.:	-20°C
operating temperatur max.:	60°C
Shock:	MIL-STD-810H Method 516.8 Procedure I
Vibration:	MIL-STD-810H Method 514.8 Procedure I
Drop:	MIL-STD-810H Method 516.8, 3 ft
voltage input DC:	19 V/DC
external power supply:	19 V/DC, 100 - 240 V/AC, DC plug
battery:	2x 11.55V, 3220mAh Li-Ion Battery (3S1P)
battery Hot-Swap:	Ja / yes

Link correlati a "L156AD-M1"

- [- Avete domande relative a questo prodotto?](#)
- [- Ulteriori prodotti di Winmate](#)

Download disponibili:

[Download Drawing L156AD-M1 Rugged Laptop.pdf](#)