



**Numero Ordine:** 25100095

**Campo testo libero 2:** 10,1 Zoll (16:10) Rugged Robotic Controller, ARM A78 + A55

**Produttore:** Winmate

**Peso:** 2.4 kg

## G101G7

### Prezzo su richiesta

Prezzi più IVA [più spese di spedizione](#)

Tempi di consegna: su richiesta

### Informazione prodotto "G101G7"

10.1" Rugged Ground Control Station ARM A78 + A55 Processor All-weather, dust and waterproof IP65 design Shock, vibration and drop resistance (MIL-STD-810H) Low-latency video SW decoder for high-resolution real-time video playback Supports WIFI, BT and optional 4G/5G Embedded TPM IC and optional OPAL SSD

article group specification:	2510
Manufacturer:	WM
Matchcode manufacturer:	nein
Manufacturer:	Wimate
series name:	Rugged Robotic Controller
Manufacturer item number:	G101G7
mechanics:	Rugged Robotic Controller
dimensions width:	36,93
dimensions height:	22,15
dimensions depth:	6,73
weight:	2,4
protection device:	IP65
colour:	Schwarz / black
cooling:	aktiv / fan cooling
Display-diagonal (inch):	10,1
aspect ratio:	16:10
resolution:	1920 x 1200
brightness:	800 cd/m <sup>2</sup>
contrast:	800:1
Display-Technology:	LCD, LED Backlight
Touch-Screen :	Projected Capacitive / Multi-Touch
usability:	Finger/ Handschuh/ finger/ glove

<b>CPU Typ:</b>	ARM Genio 510
<b>CPU Model:</b>	A78 + A55
<b>CPU speed:</b>	2,2 GHz + 2,0 GHz
<b>RAM size (MB):</b>	4096
<b>SSD design:</b>	eMMC
<b>SSD capacity:</b>	64
<b>safety:</b>	TPM 2.0
<b>WLAN:</b>	Ja / yes
<b>Bluetooth:</b>	Ja / yes
<b>WWAN:</b>	Optional / optional
<b>Camera front:</b>	Ja / yes
<b>Camera front resolution:</b>	2MP
<b>Video:</b>	2x Mirco HDMI
<b>USB:</b>	1x USB 2.0
<b>LAN:</b>	1x M8 LAN (10/100 Mbps, Max 250 Mbps)
<b>Card Slot:</b>	1x Micro SD Slot
<b>Audio:</b>	1 x Speaker
<b>Power:</b>	1x 19 V/DC, DC plug
<b>Docking connector:</b>	1x 19-pin Docking Connector
<b>operating system:</b>	Android 13.0 / Linux Ubuntu
<b>operating temperatur min.:</b>	-20°C
<b>operating temperatur max.:</b>	60°C
<b>Shock:</b>	MIL-STD-810H Method 516.8 Procedure I
<b>Vibration:</b>	MIL-STD-810H Method 514.8 Procedure I
<b>voltage input DC:</b>	19 V/DC
<b>external power supply:</b>	19 V/DC, 100 - 240 V/AC, DC plug
<b>battery:</b>	11.4V, 3500 mAh Battery (3S1P)

## Link correlati a "G101G7"

- [- Avete domande relative a questo prodotto?](#)
- [- Ulteriori prodotti di Winmate](#)

## Download disponibili:

[Download Drawing Rugged Robotic Controller G101G7 250414.pdf](#)