



**Numero Ordine:** 25100095

**Campo testo libero 2:** 10,1 Zoll (16:10) Rugged Robotic Controller, ARM A78 + A55

**Produttore:** Winmate

**Peso:** 2.4 kg

## G101G7

### Prezzo su richiesta

Prezzi più IVA [più spese di spedizione](#)

Tempi di consegna: su richiesta

### Informazione prodotto "G101G7"

1. CPU: Genio 700 2 x A78 2.2GHz + 6 x A55 2.0GHz 2. Memory: 4GB LPDDR4 3. Storage: 64GB eMMC 4. OS: Android 13.0 or Linux 5. P-Cap Touch 6. With WiFi/BT/GPS 7. Camera: 2MP Front Camera 8. With a LAN port 9. Battery: -- 11.4V, typ. 3500 mAh Li-Ion Rechargeable Internal Battery (3S1P) -- 11.4V, typ. 3500 mAh Li-Ion Rechargeable Secondary Battery (3S1P) - Operation system: Android 13.0.

article group specification:	2510
Manufacturer:	WM
Matchcode manufacturer:	nein
Manufacturer:	Wimate
series name:	Rugged Robotic Controller
Manufacturer item number:	G101G7
mechanics:	Rugged Robotic Controller
dimensions width:	36,93
dimensions height:	22,15
dimensions depth:	6,73
weight:	2,4
protection device:	IP65
colour:	Schwarz / black
cooling:	aktiv / fan cooling
Display-diagonal (inch):	10,1
aspect ratio:	16:10
resolution:	1920 x 1200
brightness:	800 cd/m <sup>2</sup>
contrast:	800:1
Display-Technology:	LCD, LED Backlight
Touch-Screen :	Projected Capacitive / Multi-Touch
usability:	Finger/ Handschuh/ finger/ glove

CPU Typ:	ARM Genio 510
CPU Model:	A78 + A55
CPU speed:	2,2 GHz + 2,0 GHz
RAM size (MB):	4096
SSD design:	eMMC
SSD capacity:	64
safety:	TPM 2.0
WLAN:	Ja / yes
Bluetooth:	Ja / yes
WWAN:	Optional / optional
Camera front:	Ja / yes
Camera front resolution:	2MP
Video:	2x Mirco HDMI
USB:	1x USB 2.0
LAN:	1x M8 LAN (10/100 Mbps, Max 250 Mbps)
Card Slot:	1x Micro SD Slot
Audio:	1 x Speaker
Power:	1x 19 V/DC, DC plug
Docking connector:	1x 19-pin Docking Connector
operating system:	Android 13.0 / Linux Ubuntu
operating temperatur min.:	-20°C
operating temperatur max.:	60°C
Shock:	MIL-STD-810H Method 516.8 Procedure I
Vibration:	MIL-STD-810H Method 514.8 Procedure I
voltage input DC:	19 V/DC
external power supply:	19 V/DC, 100 - 240 V/AC, DC plug
battery:	11.4V, 3500 mAh Battery (3S1P)

## Link correlati a "G101G7"

- [- Avete domande relative a questo prodotto?](#)
- [- Ulteriori prodotti di Winmate](#)

## Download disponibili:

- [Download Drawing Rugged Robotic Controller G101G7 250414.pdf](#)