

Numero Ordine: 25100099
Campo testo libero 2: 10,1 inch (16:10) Rugged Industrial-Tablet-PC, Intel Core i5-1235U, Windows 10 IoT
Produttore: Winmate
Peso:1.2 kg

M101AD

Prezzo su richiesta

Prezzi più IVA più spese di spedizione

Tempi di consegna: su richiesta

Informazione prodotto "M101AD"

Tablet PC for professional use Ruggedized Tablet in sturdy aluminium housing Protection class IP65 all around incl. Interfaces Shock, vibration and drop protected (MIL-STD-810H) Multi-touch (PCAP) with Glove / Rain / Stylus modes Wide range of options and accessories for data capture, communication, docking, mounting, power, peripherals and transportation The ideal partner for warehouse, logistics, automotive, outdoor, smart factory, field service etc. Long-term availability

article group specification:	2510
Manufacturer:	WM
Matchcode manufacturer:	nein
Manufacturer:	Winmate
series name:	Rugged Industrial Tablet PC
Manufacturer item number:	M101AD
mechanics:	Rugged Tablet PC
dimensions width:	27,15
dimensions height:	19,82
dimensions depth:	2,33
weight:	1,2
protection device:	IP65
colour:	Schwarz / black
cooling:	aktiv / fan cooling
Display-diagonal (inch):	10,1
aspect ratio:	16:10
resolution:	1920 x 1200
brightness:	800 cd/m²
contrast:	800:1
Display-Technology:	LCD, LED Backlight
Touch-Screen :	Projected Capactive / Multi-Touch

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de

usability:	Finger/ Handschuh/ finger/ glove
CPU Typ:	Core i5
CPU Model:	1235U
CPU speed:	3,3 GHz
CPU cores:	10
RAM size (MB):	8192
RAM max. Größe (MB:	32768
RAM Typ:	SDRAM-DDR5
SSD design:	M.2
SSD capacity:	256
SSD number:	1
safety:	TPM 2.0 und Kensington Lock
WLAN:	Ja / yes
Bluetooth:	Ja / yes
WWAN:	Optional / optional
Ethernet_connections:	1x RJ-45
Ethernet data transfer:	1 x Gigabit-LAN
Camera front:	Ja / yes
Camera front resolution:	2MP
Camera rear:	Ja / yes
Camera rear resolution:	8MP
Barcode:	Optional / optional
USB:	1x USB 3.0 (Type A), 1x USB 3.0 (Type C)
LAN:	1x RJ45 - 10/100/1000 Mbps
Card Slot:	1x Micro SDXC Slot, 1x Nano SIM Slot
Audio:	1x Audio Combo jack 3.5mm
Power:	1x 19 V/DC, DC plug
Docking connector:	1x 19-pin Docking Connector
controls:	6 Keys: Power, 5x Function
operating system:	Windows 10 IoT Enterprise
operating temperatur min.:	-20°C
operating temperatur max.:	60°C
Shock:	MIL-STD-810H Method 516.8 Procedure I
Vibration:	MIL-STD-810H Method 514.8 Procedure I
Drop:	MIL-STD-810H Method 516.8, 4 ft
voltage input DC:	19 V/DC
external power supply:	19 V/DC, 100 - 240 V/AC, DC plug
battery:	11.55V 4558 mAh (typ.) Battery (3S2P)
battery Hot-Swap:	Ja / yes

Link correlati a "M101AD"

- Avete domande relative a questo prodotto?

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de

- Ulteriori prodotti di Winmate

Download disponibili:

Download Drawing Tablet-PC M101AD 250502.pdf

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de