


Numero Ordine: 23120463

Campo testo libero 2: 12,1 Zoll (4:3) Vehicle Mount Computer VMC Serie, ARM Genio 510 A78 + A55, Android 13

Produttore: Winmate

Peso: 2.5 kg

FM12MG-V

Prezzo su richiesta

 Prezzi più IVA [più spese di spedizione](#)

Tempi di consegna: su richiesta

Informazione prodotto "FM12MG-V"

Tablet PC ready for vehicle and forklift installation Ruggedized Tablet in sturdy magnesium alloy housing Protection class IP65 all around incl. Interfaces Shock and vibration protected (MIL-STD-810H) Antiscratch resistive touch (finger & stylus) SMA connector for external antenna 10-60 V input, wide operating temperature range, mounting accessories etc. The ideal partner for warehouse, logistics, automotive, outdoor etc. Long-term availability

article group specification:	2313
Manufacturer:	WM
Matchcode manufacturer:	nein
Manufacturer:	Winnate
series name:	Vehicle Mounted Computer
Manufacturer item number:	FM12MG-V
mechanics:	Vehicle Mount Computer
dimensions width:	30,7
dimensions height:	22,5
dimensions depth:	5,7
weight:	2,5
protection device:	IP65
colour:	Schwarz / black
VESA-Mounting Interface:	VESA 75 x 75 / 100 x 100 mm
cooling:	lüfterlos / fanless
Display-diagonal (inch):	12,1
resolution:	1024 x 768
brightness:	400 cd/m²
contrast:	1000:1
Display-Technology:	LCD, LED Backlight
Touch-Screen :	Projected Capacitive / Multi-Touch

usability:	Finger/Stift/Handschuh / finger/pen/glov
CPU Typ:	ARM Genio 510
CPU Model:	A78 + A55
CPU speed:	2,0 GHz
RAM size (MB):	4096
RAM Typ:	LPDDR4
SSD capacity:	64
WLAN:	Ja / yes
Bluetooth:	Ja / yes
WWAN:	Optional / optional
Ethernet_connections:	1x RJ-45
Ethernet data transfer:	1 x Gigabit-LAN
Camera front:	Ja / yes
Camera front resolution:	2MP
USB:	1 x USB 2.0 Type C, 1 x USB 2.0 Port
serial:	2x RS-232
LAN:	1x RJ45 - 10/100/1000 Mbps
Card Slot:	1x Micro SD Slot, 1x Dual-Nano SIM Slot
Audio:	1 x Audio(Mic in & Line Out)
Power:	1x 10-60 V/DC, DC Plug
controls:	6 Keys: Power, 5x Function
operating system:	Android 13.0
operating temperatur min.:	-30°C
operating temperatur max.:	60°C
Shock:	MIL-STD-810H Method 516.8 Procedure I
Vibration:	MIL-STD-810H Method 514.8 Procedure I
voltage input DC:	10 V-60 V
battery:	Optional / optional

Link correlati a "FM12MG-V"

- [Avete domande relative a questo prodotto?](#)
- [Ulteriori prodotti di Winmate](#)